

Oil System Care

Product properties

Oil System Care increases performance, reduces oil and fuel consumption, friction and wear, protects against rust and corrosion, prevents contaminations in the oil and lubricant circulation, neutralizes harmful engine acids and preventing hardening of seals. Running noise in large aggregates such as planetary gears and translations will be reduced and it ensures continuous lubrication over the entire temperature range. Oil System Care uses ashless ingredients and is free from heavy metals.

Area of application

Use in oil and lubricant circulation of 4-stroke and diesel engines, manual gearboxes, differentials and heavy-duty equipment such as marine engines or emergency power generators as well as bearing rollers of conveyor belts. Ideal for vehicles, in which vegetable oil, rapeseed oil methyl ester (RME) or vegetable methyl ester (PME) is used.

Application

Add to oil system. We recommend an oil system cleaning with Oil System Cleaner before using this product. Total Oil capacity according to manufacturer specifications must be observed. For use in vehicles with wet clutch manufacturer's instructions must be observed. Replace in transmissions, differentials or belt systems 10 % of the amount of oil through Oil System Care.

Consumption

300 ml sufficient for 6 liters of oil. Mixing ratio: 1:20

Reaction time

while engine is running

Technical data

Physical state: viscous

Colour: brown

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.84 - 0.90 g/cm³

Water resistant

Available size	Item no.	PU
300ml	33048	24
1L	33049	12
5L	33040	4
10L	33044	1
25L	33046	1
200L	33042	1



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.