

Silicone Sealing Compound grey

Product properties

One component, elastic silicone for use in areas of high temperature. Silicone Sealing Compound Grey is an alternative to common solid gaskets.

- permanently stays elastic and stable and seals everlasting
- bridges joints of different sizes
- resistant against water, salt water, oil, fat, cleaning liquids, hydrocarbon, diluted acids and lyes and many other chemicals

Area of application

Seals metal parts (aluminum, cast, steel etc.), plastics, glass, ceramic and wood, for example oil pans, valve covers, water and oil pumps, spur gear covers, differential seals, battery cases, headlights, backlights, protection cases, thermostat cases, gear oil pans, gear cases, engine front covers, drive shaft covers etc. **Universal use:** motor and body work, heating and plumbing, air-conditioning and much more.

Application

Sealing surface must be clean and free of dust, oil and fat. Old gaskets need to be removed. Apply in the desired thickness and connect the parts.

Consumption

Depending on application

Reaction time

Skin formation: about 5-10 min/ Reaction: approx. 0,04inch/ 5 hours

Technical data

Physical state: Paste

Colour: grey

Odour: characteristic

Density at 68 °F: 1,00- 1,35 g/cm³

Density: 1,03g/cm³

Temperature resistance: -50°C bis +250°C

Working Temperature: +5°C bis +35°C

Elongation at Break: >400%

Shore Hardness A: ca. 20°

Shelf Life or Storage Life: 12 Months

Available size	Item no.	PU
200ml	39762	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

12.01.2017