

Brushwash Standard

Brushwash standard

Product properties

Brush shampoo for use in all kinds of car wash stations, especially gentle to the paintwork.

Area of application

For shampoo spray archs of car wash installations, self service pre-spray and high pressure machines and hand wash.

Application

Use the spray gun on the washing machine via a dosing pump. In this range maximum predilution 1:10. Adjust the dosage in such a way that slight foam formation is visible.

Pre-dilution: Every pre-dilution possible.

Final-dilution: max 1:500

Consumption

5-25 ml per vehicle

Reaction time

approx. 60 seconds

Technical data

Physical state: liquid

Colour: yellow

Odour: mild

pH-Value (at 68 °F): 5,0 - 7,0

Melting point: < -2 °C

Initial boiling point and boiling range: > 90 °C

Flashpoint: > 100 °C

Ignition temperature: > 300 °C

Density at 68 °F: 1,02 g/cm³

Water solubility: miscible



Available size	Item no.	PU
5kg	11120	1
25kg	11121	1
200kg	11122	1
10kg	11124	1
1kg	11126	12

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

08.03.2017