

Wheelwash Supra S Antifoam

Product properties

Highly active wheel and rim cleaner with corrosion protection and anti-foam forming properties. Specifically designed for use with wheel and rim cleaning equipment. Easily dissolves residues of dirt, oil and brake dust.

Area of application

Highly active wheel and rim cleaner with corrosion protection and anti-foam forming properties. Specifically designed for use with wheel and rim cleaning equipment. Easily dissolves residues of dirt, oil and brake dust.

Application

Application according to the dosage regulations of the device manufacturer. Please adjust the nozzles so that the cleaning agent does not come out as a fine mist, but hits the rim in liquid state.

Suitable to clean steel and sealed aluminum wheels and rims

ATTENTION

Do not let the cleaning mixture dry!

Do not apply on hot wheel rims!

Do not use on acid sensitive surfaces!

Before using the product, check the acid resistance on the spray device and flooring.

Pre-dilution: Every pre-dilution possible

Final-dilution: pure up to 1 : 20 (car wash)

Consumption

12-19 ml per vehicle

Reaction time

max. 45 sec. (pure)

Technical data

Physical state: liquid

Colour: pink

Odour: mild

pH-Value (at 68 °F): 0,5

Melting point: < 0 °C

Boiling point (ERBP): > 80 °C

Flashpoint: > 100 °C

Ignition temperature: > 200 °C

Density at 68 °F: 1,1 - 1,2 g/cm³

Water soluble

Insusceptible to Frost



Available size	Item no.	PU
5kg	11290	1
25kg	11291	1
200kg	11292	1
10kg	11294	1

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advice. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de